



Date: _____ Driver: BALASTRI DARIO
 Event: EUROPEAN CHAMPION Car: G-4 S
 Track: HEENSTED HOLLAND Weight: _____

SETUP SHEET



TRACK CONDITIONS

Surface: Smooth Med. Bumpy
 Size: Open Med. Tight
 Traction: High Med. Low

Track Temp/Air Temp: ° 15°
 Note: "SHORT STEP"

FRONT SUSPENSION

TOE ANGLE

 Front Width: 198 mm
 Anti-Roll Bar: 0
 Diff. Fluid: 50000 wt
 One Way
 Solid Axle
 Toe Angle: +1°

FRONT CAMBER

 Front Camber: L25 R25
 Front Ride Height: 5 mm
 Front Droop: 3 mm
 Caster: NEUTRAL mm
 ▶ SHOCK
 Shock Length: _____ mm
 Thread Length: _____ mm
 Oil: 300 wt
 Piston: 2 HOLE
 Spring: GREY HUGEN mm
 ▶ TIRE
 Front Tire: KYOSHO
 Shore: L37° R37°
 Diameter(Start): L/R 60/62 mm
 Diameter(Finish): L/R / / mm

TOWER MOUNTING

 Front Droop: _____ mm
 Arm Mounting

STEERING

 Caster: _____ mm
 Thread Length

 Shock Length

REAR SUSPENSION

TOE ANGLE

 Rear Width: 198 mm
 Anti-Roll Bar: HUGEN 2, 1mm
 Diff. Fluid: 10000 wt
 Solid Axle
 Toe Angle: 3,5°

REAR CAMBER

 Rear Camber: L3° R3°
 Rear Ride Height: 6 mm
 Rear Droop: 4 mm
 ▶ SHOCK
 Shock Length: _____ mm
 Thread Length: _____ mm
 Oil: 350 wt
 Piston: 2 HOLE
 Spring: T.H. 16 mm
 ▶ TIRE
 Front Tire: KYOSHO
 Shore: L37° R37°
 Diameter(Start): L/R 62/64 mm
 Diameter(Finish): L/R / / mm

TOWER MOUNTING

 Camber Link

 Rear Droop: _____ mm
 Arm Mounting

Pulley

Front Side Pulley: 27 T
 Rear Side Pulley: 19 T
 Brake Pulley: 21 T

CLUTCH

Gear Ratio: 1st 16T/51T
 2nd 21T/45T
 Clutch Set Type:
 3 Shoe Push Type
 Clutch Spring: 1.8 mm
 Clutch weight: 2
 Clutch Shoe: BLACK
 Engine: NOVAROSS
 Plug: NOVAROSS
 Fuel: NOVAROSS
 Manifold: _____
 Pipe: NOVAROSS
 Pipe Length: _____ mm

Note: _____

Body

Body: STRATUS 31
 Radio: SANWA
 ST. Servo: SANWA
 TH. Servo: SANWA

COMMENTS

Race Time / Lap: _____
 Best Lap Time: _____
 Position: _____
 Notes: _____
